IHI PREBREAKER



- * Size reduction of raw products.
- * Rotor diameters of 15" and 24".
- * Hard faced rotor hammers in single or double hook configurations.
- * Hard faced anvils in base pan and discharge head.
- * Hard faced pan and head for extended life
- * Orifice plate or disc style discharge controls product size.
- * Heavy steel plate construction for industrial applications.
- * Available in carbon or stainless steel, edible design optional.
- * Repairable services and replacement components for existing machines.



INDUSTRIAL HARDFACING, INC

218 EAST MAIN STREET

LAMONI, IA 50140 FAX: 641.784.8370

PHONE: 641.784.6921 TOLL FREE: 800.247.7778 FAX:

www.industhard.com sales@industhard.com





Motor to Gearbox direct coupling

↓ INLET ↓


| Section | Se

DISCHARGE

Gearbox to Rotor direct coupling



Hardface diamond weld for extended life



Prebreaker inlet

Model	A-Length* w/o drive	A-Length w/drive	B-Length* w/o drive	C-Length* w/o drive	Motor HP	Approx. Capacity
FPR15	112"	186"	36"	42"	100-150 HP	36,000 Lbs per Hr
FPR24	115"	200"	44"	48"	150-200 HP	54,000 Lbs per Hr

*EXCLUDES DRIVE COMPONENTS Note: Dimensions subject to change without notice, capacities vary per application.

